



Product Description

1. Product Name	Basetrac® Duo PET 50 B15		
2. Product Description	Biaxial geogrid plus nonwoven geotextile for base reinforcement.		
3. Raw Materials used			
Raw Material of the geogrid:	MD / CMD	PET	
Raw Material of the nonwoven:		150 g/m ² PP	

Technical data

01. Mass per unit area (DIN EN ISO 9864)		g/m ²	≅ 330
02. Nominal Tensile Strength (DIN EN ISO 10319)	MD CMD	kN/m kN/m	≥ 50 ≥ 50
03. Strain at Nominal Tensile Strength (DIN EN ISO 10319)	MD CMD	% %	≤ 10 ≤ 10
04. Tensile Strength at 2 % Strain (DIN EN ISO 10319)	MD CMD	kN/m kN/m	≥ 6 ≥ 6
05. Tensile Strength at 5 % Strain (DIN EN ISO 10319)	MD CMD	kN/m kN/m	≥ 20 ≥ 20
06. Mesh Size of the Geogrid		mm	25 x 25
07. Opening Size of the Nonwoven (DIN EN ISO 12956)		µm	≅ 120
08. Water Permeability Index Normal to the Plane (nonwoven) (EN ISO 11058)		m/s	≅ 90 x 10 ⁻³
09. Standard Roll Dimensions (width x length)		m x m	5,00 x 100
10. Durability (acc. to EN 13249: 2015 ff.)			Predicted to be durable for 100 years in natural soils with 4 ≤ pH ≤ 9 and soil temperatures ≤ 25 °C.